



**D3767-1 UPPER RAIL**

- NOTES:**
- 1) MATERIAL: 6061-T6 OR 6061-T62 ALUMINUM TUBING (1.00" OD X 0.065" WALL) PER WW-T-700/6 OR AMS 4080 OR AMS 4082 OR QQ-A-200/8 OR AMS-QQ-A-225/8 (REF. DART SPEC. M6061T6T1.000W.065)
  - 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
  - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
  - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
  - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
  - 6) IDENTIFICATION: N/A
  - 7) WEIGHT: 0.62 lbs

B	CHANGE HOLE SIZE TO 0.201, SHIFT HOLES FOR ATTACHING FRAME BY 0.125, ADD HOLE AT 16.10	HS	08.06.23
A	NEW ISSUE	HS	08.06.04
REV.	DESCRIPTION	BY	DATE
DESIGN	HS	<b>DART AEROSPACE LTD</b> HAWKESBURY, ONTARIO, CANADA	
DRAWN	HS		
CHECKED		DRAWING NO.	REV. B
MFG. APPR.		D3767	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		UPPER RAIL	NTS
DATE	08.06.23	COPYRIGHT © 2008 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	